



## We Got Your Six. We protect those who serve us

## JACKAL6 BODY 10 FEATURES

The Jackal6 Body 10 has a concise yet simple design that makes this body worn camera (BWC) easy to use. The Body 10 comes equipped with a large one-touch action button, continuous video recording, highresolution photo capture, automatic infrared (IR) illumination and secure Wi-Fi video connectivity via desktop and mobile devices.

**JACKAL6** 

**High-Definition (HD) VIDEO:** Record crystal clear video and capture every detail with a 140-degree field of view.

**HIGH CAPICITY BATTERY:** Continuous video recording up to 10 hours on a single charge.

**PRE/POST-EVENT BUFFER:** Configure your pre/postevent buffer time to capture before and after an event.

**AUTOMATIC IR:** Record more and witness more during those low-light situations.

**WEATHERPROOF:** Built tough to withstand most extreme weather conditions and climate events.

**EMBEDDED SECURITY:** Evidence is locally encrypted on the camera to protect data at all times.

**DEVICE LOGGING:** Watermark videos and photos with a unique ID and date/time stamp.

**MOBILE APP:** Stream and replay videos right on your mobile device with Jackal6 Vision.



## JACKAL6 BODY 10 SPECIFICATIONS

VIDEO RESOLUTION: Configurable up to 1080p; 2506x1080p@30fps, 2304x1296p@30fps, 1920x1080p@30fps, 1280x720p@30/60fps, 848x480p@30/60fps, 640x480p@30/60fps FIELD OF VIEW: 140-degree wide angle **INFRARED LED:** Two IR leds; Up to 49ft / 15m working range PRE/POST-EVENT BUFFER: Pre-record from 5 to 30 seconds; Post-record for 10/30/60 seconds **STORAGE VOLUME:** 32gb / 64gb\* (optional) COMMUNICATIONS: Built-in WiFi; IEEE 802.11 standard **GLOBAL POSITIONING:** Yes\* (optional) BATTERY CAPACITY: Continuous video recording up to 10 hours; 3200mAh Lithium-Ion **CHARGING TIME:** Four hours for full charge WEIGHT: 4.4oz / 125g **DEVICE SIZE:** 3in x 2.2in x .8in / 77mm x 56mm x 22mm WEATHER RESISTANCE: IP65; Resists dust and water **OPERATING TEMPERATURE:** -40 °f to 140 °f / -40 °C to 60 °C STORAGE TEMPERATURE: -4 °f to 131 °f / -20 °C to 55 °C WARRANTY: One year from date of receipt with extended full five-year warranty options